# **Amarok Single Cab Specification**

SC



New Amarok Specification	PR #	2.0 TDI 125kW 4Motion Amarok Single Cab
Engine		
Cylinders		4
Capacity (cm3)		1996
Output (kW @ r/min)		125 @ 3 500
Torque (Nm @ r/min)		405 @ 1 750 - 2 500
CO2 emissions (g/km)		187
Transmission		
6-speed manual		Х
Performance		
Top speed (km/h)		180
Fuel consumption		
Combined		8.4
Body		
Black bumper in front	2JK	Х
Black bumper in rear	2K2	Х
Black exterior mirror housings and door handles	6FI	Х
Black radiator grille	6КС	Х
Black rear gate handle	6V3	Х
Exterior mirrors, power-adjustable and power-folding	6XB	Х
Heated rear window	8P1	Х
Interior door handles in Black	5JC	Х
Laminated windshield	4GF	Х
Load support including protection frame on the rear cabin wall	2Y1	Х
Mud flaps at front and rear	6N2	Х
Tie-downs on the cargo area and rail for the side panel of the cargo area	6B2	Х
Chassis		
255/70 R16 111T tires	H6Q	Х

16-inch steel wheels 255/70 R16, spare wheel with original equipment tire	C2F	Х
Differential lock in rear	1Y4	Х
Part-time 4MOTION (2H, 4H, 4L)	OR3	Х
Standard suspension system	1BA	Х
Safety Equipment		
3-point belts, in addition height-adjustable in 1st row of seats	3QB	Х
Driver and front passenger airbags with front passenger airbag deactivation	4UF	Х
Electronic Stability Control	1AK	Х
LED headlamps	8EX	Х
Parking brake	UH1	Х
Rear combination lamps	8SA	Х
Side and curtain airbags	4X7	Х
Warning signal and warning lamp for front seat belts not fastened	9P3	Х
Without seat belt pretensioners in 2nd row of seats	4RA	Х
Interior Equipment		
2 reading lights for driver and front passenger in overhead console	7N3	Х
2 speakers	8RD	Х
Vinyl floor covering	5AC	Х
Driver seat with 6-way adjustment and front passenger seat with 4-way adjustment	3PN	Х
Gearshift lever (manual transmission)	0G8	Х
Gearshift/selector lever knob	6R0	Х
Glove compartment	4Z1	Х
Headliner (in Stone Gray)	6NT	Х
Multi-function steering wheel	1XR	Х
Particle filter	2V1	Х
Roof grab handles, rigid grab handles, on A-pillar	5N7	Х
Seat trim covers in fabric	NOA	Х
Sun visor on driver and front passenger side	5XK	Х
Without floor mats	OTA	Х
Functional Equipment		
2 vehicle keys	8QM	Х

Air conditioning system with manual control	9AP	Х
AM/FM antenna	QVO	Х
Anti-theft alarm system with interior monitoring, backup horn and towing protection	7AF	Х
Central locking system with SAFELOCK, with radio remote control	4K3	Х
Dashboard	4N0	Х
Digital cockpit with 20.3-cm (8-inch) color screen	9Q1	Х
Emission standard EU4	OGG	Х
Headlight range control	8K1	Х
Heating and fresh air system	9M0	Х
nfotainment system with 25.6cm (10.1-inch) color screen	18P	Х
ntermittent windshield wiper control with rain sensor	8N3	Х
_ED cargo area lighting	9CW	Х
Power window regulators in front (single cab)	4R0	Х
Rear gate with rear gate latch	ЗRК	Х
Removable trailer hitch, 7-pin	1D1, IP3	Х
Dimensions / Capacities		
Fuel tank (l)		80
Nading depth (mm)		800
_ength (mm)		5 350
Height (mm)		1 884
Nidth (mm) excluding side mirrors		1 910
Wheelbase (mm)		3 270
Turning circle (m)		12.93
Ground clearance (mm) - measured under the front axle		237
Approach / Departure angle (°) (excl. trailer hitch)		29 / 26
Ramp angle (°)		21
_oad compartment length (mm)		2332
oad compartment width between wheelhouses (mm)		1227
_oad compartment height of the side walls (mm)		529
Weights		
Roof load limit (kg) (Moving/Static)		85 / 350

Axle load limit front / rear (kg)	1 450 / 1 959
Kerb Mass (minimum) without driver and with fuel (kg)	1 947
Maximum payload capacity (kg) ~ based on minimum kerb mass	1 243
Gross Vehicle Mass (GVM) (kg)	3 190
Towing capacity: unbraked (kg)	750
Towing capacity: braked (kg)	3 500
Gross Combined Mass (GCM) (kg)	6 150
Guarantees	
3-year / 120 000 km manufacturer warranty	Х
Disclaimer	

Dimensions, capacities and abilities apply to standard vehicles. Actual consumption will vary with vehicle loading, driving style, climatic and road conditions. The above information is effective as at January 2024 and is subject to change.

Classification:Internal and External CSD document class 8.3/ retention period: 15 years from creation Classification:Internal and External CSD document class 8.3/ retention period: 15 years from creation



## **Amarok Life Specification**

Life



### **Amarok Life Specification**

New Amarok Specification	PR #	2.0 TDI 125kW 4Motion Life	2.0 BiTDI 154kW 4Motion Life Automatic
Engine			
Cylinders		4	4
Capacity (cm3)		1996	1996
Output (kW @ r/min)		125 @ 3 500	154 @ 3 750
Torque (Nm @ r/min)		405 @ 1 750 - 2 500	500 @ 1 750 - 2 000
CO2 emissions (g/km)		187	195
Transmission			
6-speed manual		Х	_
10-speed automatic (shift by wire)		-	Х
Performance			
Top speed (km/h)		180	180
Fuel consumption			
Combined		7.1	7.5
Body			
Black bumper in rear	2K2	Х	Х
Black radiator grille	6KC	Х	Х
Body-colored bumper in front	2JF	Х	Х
Body-colored exterior mirror housings and door handles	6FA	Х	Х
Body-colored rear gate handle	6V2	Х	Х
Side steps with chrome inserts	QT7	Х	Х
Dark-tinted (privacy glass) rear side windows and rear window	QL5	Х	Х
Exterior mirrors, power-adjustable and power-folding	6XB	Х	Х
Fuel filler door, non-lockable	2W0	Х	Х
Heated rear window	8P1	Х	Х
nterior door handles in Black	6JC	Х	Х
Laminated windshield	4GF	Х	Х
Mud flaps at front and rear	6N2	Х	Х

Tie-downs on the cargo area	6B0	Х	Х
Chassis			
255/70 R17 112T all-terran tires	H2A	Х	_
Alloy wheels "Combra" 7.5 x 17 all-terrain tires, spare wheel (steel) with original equip- ment tire	ZOQ	Х	_
255/65 R18 all-terrain tires	84K	-	Х
Alloy wheels "Amadora" 7.5 x 18, all-terrain tires, spare wheel (alloy wheel) with original equipment tire	Z8H	-	Х
Differential lock in rear	1Y4	Х	Х
Part-time 4MOTION (2H, 4H, 4L)	OR3	Х	Х
Standard suspension system	1BA	Х	Х
Wheel locks	1PB	Х	Х
Safety Equipment			
3 head restraints in 2nd row of seats	3Q1	Х	Х
3-point belts in 2nd row of seats	4PP	Х	Х
3-point belts, in addition height-adjustable in 1st row of seats	3QB	Х	Х
Child seat anchors ISOFIX on outer rear seats, i-Size compatible	3B5	Х	Х
Driver and front passenger airbags with front passenger airbag deactivation	4UF	Х	Х
Electromechanical parking brake	UH2	Х	Х
Electronic Stability Control	1AK	Х	Х
LED front fog lamps	8WH	Х	Х
LED headlamps	8EX	Х	Х
Rear combination lamps	8SA	Х	Х
Top tether	3G3	Х	Х
Warning signal and warning lamp for front seat belts not fastened	9P3	Х	Х
Interior Equipment			
2 reading lights for driver and front passenger with glasses compartment in overhead console	7N2	Х	Х
3-seater bench in 2nd row of seats	3UH	Х	Х
6 speakers	8RL	Х	Х
Carpet floor covering	5AD	Х	Х
Center armrest in rear on 3-seater bench	6D1	Х	Х
Driver and front passenger seats with 8-way adjustment	3PQ	Х	Х

Driver seat with map pocket	4U6	Х	Х
Gearshift/selector lever knob, leather	6R2	Х	Х
Glove compartment, illuminated	4Z5	Х	Х
Headliner (in Stone Gray)	6NT	Х	Х
Leather-wrapped multi-function steering wheel	2ZU	Х	Х
Particle filter	2V1	Х	Х
Roof grab handles on driver side and front passenger side, rigid grab handles on A-pillar	5N3	Х	Х
Seat trim covers in fabric Life	NOK	Х	Х
Sun visor on driver and front passenger side with illuminated vanity mirror	5XA	Х	Х
Rubber floor mats	OTG	Х	Х
Functional Equipment			
2 vehicle keys	8QM	Х	Х
Air conditioning system with manual control	9AP	Х	Х
AM/FM antenna	QVO	Х	Х
Central locking system with SAFELOCK, with radio remote control	4K3	Х	Х
Cruise control system with speed limiter	8T3	Х	Х
Digital cockpit with 20.3-cm (8-inch) color screen	9Q1	Х	Х
Headlight range control	8K1	Х	Х
Heating and fresh air system	9M0	Х	Х
Infotainment system with 25.6-cm (10.1-inch) color touch screen	18P	Х	Х
Intermittent windshield wiper control with rain sensor	8N3	Х	Х
LED cargo area lighting	9CW	Х	Х
Park Distance Control in front and rear	7X2	Х	Х
Power windows in front and rear	4R1	Х	Х
Rear gate lockable via central locking system	3RQ	Х	Х
Rear view camera system	KA1	Х	Х
Removable trailer hitch, 7-pin	1D1, IP3	Х	Х
Dimensions / Capacities			
Fuel tank (l)		80	80
Wading depth (mm)		800	800
Length (mm)		5 350	5 350

Height (mm)	1 884	1 884
Width (mm)	1 910	1 910
Wheelbase (mm)	3 270	3 270
Turning circle (m)	12.93	12.93
Ground clearance (mm) - measured under the front axle	237	237
Approach / Departure angle (°) (excl. trailer hitch)	30 / 26	30 / 26
Ramp angle (°)	21	21
Load compartment length (mm)	1 624	1 624
Load compartment width between wheelhouses (mm)	1 227	1 227
Load compartment height of the side walls (mm)	529	529
Weights		
Roof load limit (kg) (Moving/Static)	85 / 350	85 / 350
Axle load limit front / rear (kg)	1 450 / 1 959	1 450 / 1 959
Kerb Mass (minimum) without driver and with fuel (kg)	2 069	2 106
Maximum payload capacity (kg) ~ based on minimum kerb mass	1 162	1 124
Gross Vehicle Mass (GVM) (kg)	3 230	3 230
Towing capacity: unbraked (kg)	750	750
Towing capacity: braked (kg)	3 500	3 500
Gross Combined Mass (GCM) (kg)	6 150	6 500
Guarantees		
3-year / 120 000 km manufacturer warranty	Х	Х
Disclaimer		

Dimensions, capacities and abilities apply to standard vehicles. Actual consumption will vary with vehicle loading, driving style, climatic and road conditions. The above information is effective as at January 2024 and is subject to change.

Classification:Internal and External CSD document class 8.3/ retention period: 15 years from creation Classification:Internal and External CSD document class 8.3/ retention period: 15 years from creation



# **Amarok Style Specification**

Style

### Amarok Style Specification

New Amarok Specification	PR #	2.0 BiTDI 154kW 4Motion Style Automatic
Engine		
Cylinders		4
Capacity (cm3)		1996
Output (kW @ r/min)		154 @ 3 750
Forque (Nm @ r/min)		500 @ 1 750 - 2 000
CO2 emissions (g/km)		195
Transmission		
10-speed automatic (shift by wire)		Х
Performance		
op speed (km/h)		180
uel consumption		
Combined		7.5
Body		
Black bumper in rear with chrome-plated styling elements	2K1	Х
Body-colored bumper in front	2JF	Х
Body-colored exterior mirror housings and door handles	6FA	Х
Body-colored rear gate handle	6V2	Х
Side steps with chrome inserts	QT8	Х
Dark-tinted (privacy glass) rear side windows and rear window	QL5	Х
Exterior mirrors, power-adjustable, heated and power-folding, with surround lighting	6XE	Х
uel filler door, non-lockable	2W0	Х
leated rear window	8P1	Х
nterior door handles in chrome	6JE	Х
aminated windshield made of insulating glass	4GL	Х
oad compartment trim in plastic with 12-V outlet in side panel	3GP	Х
Mud flaps at front and rear	6N2	Х
tyling bar in chrome	IB2	Х

Radiator grille with chrome bezel	6KA	X
Tie-downs on the cargo area	6B0	X
Chassis		
All-terrain tires 255/65 R18	84K	Х
Alloy wheels "Amadora" 7.5 x 18, all-terrain tires, spare wheel (alloy wheel) with original equipment tire	Z8H	Х
Part-time 4MOTION (2H, 4H, 4L)	OR3	Х
Differential lock in rear	1Y4	Х
Standard suspension system	1BA	Х
Wheel locks	1PB	Х
Safety Equipment		
3 head restraints in 2nd row of seats	3Q1	Х
3-point belts in 2nd row of seats	4PP	Х
3-point belts, in addition height-adjustable in 1st row of seats	3QB	Х
Driver and front passenger airbags with front passenger airbag deactivation	4UF	Х
Autonomous Emergency Braking with Pedestrian and Cyclist Monitoring	UZ1	Х
Child seat anchors ISOFIX on outer rear seats, i-Size compatible	3B5	Х
Electromechanical parking brake	UH2	Х
Electronic Stability Control	1AK	Х
LED front fog lamps	8WH	Х
LED headlamps	8EX	Х
Rear combination lamps	8SA	Х
Tire Pressure Monitoring System (direct measurement)	7K3	Х
Top tether	3G3	Х
Warning signal and warning lamp for front seat belts not fastened	9P3	Х
Interior Equipment		
10-way power-adjustable driver seat and 8-way adjustable front passenger seat	3PZ	Х
2 reading lights for driver and front passenger with glasses compartment in overhead console	7N2	Х
3-seater bench in 2nd row of seats	3UH	Х
6 speakers	8RL	Х
Automatic transmission selector lever with shift-by-wire technology	0G2	Х
Carpet floor covering	5AD	Х

Center armrest in rear on 3-seater bench	6D1	Х
Driver seat with map pocket	4U6	Х
Gearshift/selector lever knob, leather	6R2	Х
Glove compartment, illuminated and lockable	4Z3	Х
Headliner (in Stone Gray)	6NT	Х
Leather-wrapped multi-function steering wheel	2ZU	Х
Particle filter	2V1	Х
Roof grab handles on driver side and front passenger side, rigid grab handles on A-pillar	5N3	Х
Seat heater for both seats in cab, left and right individually controllable	4A3	Х
Seat trim covers Style with ArtVelours microfleece insert	NOL	X
Sun visor on driver and front passenger side with illuminated vanity mirror	5XA	Х
Velour floor mats	OTD	Х
Functional Equipment		
1 USB charging socket on the interior rearview mirror	UF1	Х
120-V/230-V outlet in rear center console and in cargo area	9Z2	Х
2 vehicle keys	8QJ	X
2-zone Climatronic air conditioning system	KH4	Х
AM/FM antenna	QVO	Х
Automatic Post-Collision Braking System	7W1	Х
Central locking system with keyless locking and starting system Keyless Access with SAFELOCK	416	Х
Cruise control system with speed limiter	8T3	Х
Premium dashboard in leather look (vinyl)	4N3	Х
Digital cockpit with 31.2-cm (12.3-inch) color screen	9Q2	Х
Headlight range control	8K1	Х
Heating and fresh air system	9M0	Х
High-beam control Light Assist	8Q1	Х
Inductive charging feature	EK2	Х
Infotainment system with 30.5-cm (12-inch) color touch screen for navigation	18X	Х
Intermittent windshield wiper control with rain sensor	8N3	Х
LED cargo area lighting	9CW	Х
Lane keeping system Lane Assist	7Y2	Х

Rear gate lockable via central locking system3RQXRear view camera system, analogKA1XRemovable trailer hitch, 7-pmJD1, IP3XDimensions / CapacitiesDimensions / CapacitiesB00Ucal tank (I)800800Uading depth (mm)5.550804Longth (mm)1.884940Width (mm)1.884940Width (mm)2.701.910Turning circle (m)3.0726807Remo angle (*) (xect. trailer hitch)30.726807Remo angle (*) (xect. trailer hitch)30.726807Remo angle (*) (xect. trailer hitch)1.6241.227Load compartment length (mm)1.6241.227Load compartment width between wheelhouses (mm)1.2271.227Load compartment width between wheelhouses (mm)1.2271.490/1.959Keb Mass (minimum) widtou driver and with fuel (kg)85.73503.60Akeload limit (kg) (Moving/Static)85.73503.280Keb Mass (minimum) widtou driver and with fuel (kg)3.2803.280Towing capacity (kg)- based on minimum kerb mass1.1483.280Towing capacity inbraked (kg)3.2803.500	Park Distance Control in front and rear	7X2	Х
Kan Kal x   Removable traiter hitch, 7-pin 1D1, IP3 X   Dimensions / Capacities 80   Fuel tack (j) 80   Wading depth (mm) 5350   Lingth (mm) 5350   Height (mm) 1884   Wild (non) 1910   Wheelses (mm) 2927   Turning circle (m) 225   Approach / Departure angle (*) (excl. trailer hitch) 30 / 26   Ramp angle (*) 21   Load compartment keight of the side walls (mm) 1227   Load compartment keight of the side walls (mm) 1227   Load compartment keight of the side walls (mm) 1227   Load compartment keight of the side walls (mm) 1227   Kerb load limit (kg) (Moving/Static) 85 / 350   Ake load limit tont / nor (kg) 1490 / 1959   Kerb load capartment keight of the side walls (mm) 2132   Maimum payload capacity (kg) - based on minimum kerb mass 1148   Goos Vehicle Mass (KVV) (kg) 3280   Towing capacity: braked (kg) 3280   Towing capacity: braked (kg) 350	Power windows in front and rear	4R1	Х
Removable trailer hich, 7-pin 1D1, IP3 X   Dimensions / Capacities 80   Fuel tank (I) 80   Wading depth (mm) 800   Length (Imm) 5.350   Height (mm) 5.350   Height (mm) 1.884   Width (mn) 1.910   Whenbase (mm) 3.270   Turning circle (m) 12.93   Ground clearance (mm) - measured under the front axle 235   Appraach / Departure angle (*) (excl. trailer hitch) 30 / 26   Ramp angle (*) 2.1   Lead compartment length (mm) 1.62/4   Lead compartment width between wheelhouses (mm) 1.227   Lead compartment width between wheelhouses (mm) 1.227   Lead compartment width between wheelhouses (mm) 1.227   Lead compartment width between wheelhouses (mm) 5.29   Weights 1.490 / 1.959   Kerb Mass (minurum) without driver and with fuel (kg) 2.132   Maximum payload capacity (kg) - based on minum kerb mass 1.148   Gross Whiele Mass (civVI) (kg) 3.280   Towing capacity: unbraked (kg) <	Rear gate lockable via central locking system	3RQ	Х
Dimensions / Capacities 80   Fuel tark (I) 80   Wading depth (mm) 800   Length (mm) 800   Length (mm) 5350   Height (mm) 1884   Width (mm) 1910   Wheelbase (mm) 3270   Turning circle (m) 12.93   Ground clearance (mm) - measured under the front axle 235   Approach / Departure angle (?) (excl. trailer hitch) 30 / 26   Ram pangle (?) 21   Load compartment length (mm) 1624   Load compartment length (mm) 1227   Load compartment height of the side walls (mm) 529   Weights 1400 / 1959   Kerb Mass (minimum) without driver and with fuel (kg) 2132   Maximum payload capacity (kg) - based on minimum kerb mass 1148   Gross Weitche Mass (GVM) (kg) 3280   Towing capacity: unbraked (kg) 750   Towing capacity: unbraked (kg) 3500	Rear view camera system, analog	KA1	Х
Fuel tank (I) 80   Wading depth (mm) 800   Length (mm) 5 350   Height (mm) 1 884   Width (mm) 1 910   Wheelbase (mm) 3 270   Turning circle (m) 3 270   Sound clearance (mm) - measured under the front axle 235   Approach / Departure angle (°) (excl. trailer hitch) 30 / 26   Ramp angle (°) 21   Load compartment length (mm) 1 624   Load compartment keight of the side walls (mm) 529   Weights 529   Weights 85 / 350   Axle load limit (kg) (Moving/Statc) 85 / 350   Axle load limit (kg) (Moving/Statc) 1490 / 1959   Keb Mass (minimum) without driver and with fuel (kg) 2 132   Maximum payload capacity (kg) - based on minimum kerb mass 1 148   Gross Vehicle Mass (GVM) (kg) 3 280   Towing capacity: unbraked (kg) 7 50   Towing capacity: unbraked (kg) 3 500	Removable trailer hitch, 7-pin	1D1, IP3	Х
Waing dept (rm) 600   Length (rm) 5 350   Height (rm) 1 884   Width (rm) 1 910   Wheelbase (rm) 3 270   Turning circle (rm) 3 270   Turning circle (rm) 3 270   Ground clearance (rmm) - measured under the front axle 235   Approach / Departure angle (°) (excl. trailer hitch) 30 / 260   Ramp angle (°) 21   Load compartment length (rmm) 1 624   Load compartment length (rmm) 1 624   Load compartment height of the side walls (rmm) 529   Weights 529   Weights 1 490 / 1 959   Keib load limit (kg) (Moving/Static) 85 / 350   Axle load limit front / rear (kg) 2 132   Maximum payload capacity (kg) - based on minimum kerb mass 1 1448   Gross Vehicle Mass (GVM) (kg) 3 280   Towing capacity: unbraked (kg) 750	Dimensions / Capacities		
Length (mm) 5 350   Height (mm) 1 884   Width (mm) 1 910   Wheelbase (mm) 3 270   Turning circle (m) 1 2.93   Ground clearance (mm) - measured under the front axle 235   Approach / Departure angle (°) (excl. trailer hitch) 30 / 26   Ramp angle (°) 21   Load compartment length (mm) 1 624   Load compartment length the side walls (mm) 3270   Weights 227   Weights 235   Axle load limit (kg) (Moving/Static) 85 / 350   Axle load limit (kg) (Moving/Static) 85 / 350   Axle load limit fort / rear (kg) 1 148   Gross Vehicle Mass (GVM) (kg) 3 280   Towing capacity: unbraked (kg) 3 280   Towing capacity: unbraked (kg) 3 500	Fuel tank (l)		80
Height (mm) 1884   Width (mm) 1910   Wheelbase (mm) 3 270   Turning circle (m) 12.93   Ground clearance (mm) - measured under the front axle 235   Approach / Departure angle (*) (excl. trailer hitch) 30 / 26   Ramp angle (*) 21   Load compartment length (mm) 1624   Load compartment length (mm) 1227   Load compartment height of the side walls (mm) 529   Weights 529   Words Limit (kg) (Moving/Static) 85 / 350   Ake load limit (kg) (Moving/Static) 85 / 350   Kerb Mass (minimum) without driver and with fuel (kg) 2 132   Maximum payload capacity (kg) - based on minimum kerb mass 1 148   Gross Vehicle Mass (GVM) (kg) 3 280   Towing capacity: unbraked (kg) 750   Towing capacity: braked (kg) 3 500	Wading depth (mm)		800
Width (mm) 1 910   Width (mm) 3 270   Turning circle (m) 12.93   Ground clearance (mm) - measured under the front axle 235   Approach / Departure angle (°) (excl. trailer hitch) 30 / 26   Ramp angle (°) 21   Load compartment length (mm) 1 624   Load compartment length (mm) 1 227   Load compartment height of the side walls (mm) 529   Weights 529   Roof Load limit (kg) (Moving/Static) 85 / 350   Akle load limit front / rear (kg) 1 490 / 1 959   Kerb Mass (minimum) without driver and with fuel (kg) 2 132   Maximum payload capacity (kg) ~ based on minimum kerb mass 1 148   Gross Vehicle Mass (GVM) (kg) 3 280   Towing capacity: unbraked (kg) 750   Towing capacity: braked (kg) 3 500	Length (mm)		5 350
Wheelbase (mm)3 270Turning circle (m)12.93Ground clearance (mm) - measured under the front axle235Approach / Departure angle (°) (excl. trailer hitch)30 / 26Ramp angle (°)21Load compartment length (mm)1 624Load compartment width between wheelhouses (mm)1 227Load compartment height of the side walls (mm)529Weights529Roof load limit (kg) (Moving/Static)85 / 350Axle load limit (kg) (Moving/Static)85 / 350Axle load limit front / rear (kg)1 490 / 1 959Kerb Mass (minimum) without driver and with fuel (kg)2 132Maximum payload capacity (kg) - based on minimum kerb mass1 148Gross Vehicle Mass (GVM) (kg)3 280Towing capacity: unbraked (kg)750Towing capacity: braked (kg)3 500	Height (mm)		1 884
Turning circle (m)12.93Ground clearance (mm) - measured under the front axle235Approach / Departure angle (°) (excl. trailer hitch)30 / 26Ramp angle (°)21Load compartment length (mm)1 624Load compartment height of the side walls (mm)1 227Load compartment height of the side walls (mm)529Weights750Roof load limit (kg) (Moving/Static)85 / 350Axle load limit front / rear (kg)1 4490 / 1 959Kerb Mass (minimum) without driver and with fuel (kg)2 132Maximum payload capacity (kg) - based on minimum kerb mass1 148Gross Vehicle Mass (CVM) (kg)3 280Towing capacity: unbraked (kg)750Towing capacity: braked (kg)3 500	Width (mm)		1 910
Ground clearance (mm) - measured under the front axle235Approach / Departure angle (°) (excl. trailer hitch)30 / 26Ramp angle (°)21Load compartment length (mm)1 624Load compartment length (mm)1 227Load compartment kight of the side walls (mm)529Veights5Roof load limit (kg) (Moving/Static)85 / 350Axle load limit front / rear (kg)1 490 / 1 959Kerb Mass (minimum) without driver and with fuel (kg)2 132Maximum payload capacity (kg) - based on minimum kerb mass1 148Gross Vehicle Mass (GVM) (kg)3 280Towing capacity: braked (kg)750Towing capacity: braked (kg)3 500	Wheelbase (mm)		3 270
Approach / Departure angle (°) (excl. trailer hitch)30 / 26Ramp angle (°)21Load compartment length (mm)1.624Load compartment width between wheelhouses (mm)1.227Load compartment height of the side walls (mm)529Weights85 / 350Roof load limit (kg) (Moving/Static)85 / 350Axle load limit front / rear (kg)1.490 / 1.959Kerb Mass (minimum) without driver and with fuel (kg)2.132Maximum payload capacity (kg) - based on minimum kerb mass1.148Gross Vehicle Mass (GVM) (kg)3.280Towing capacity: unbraked (kg)750Towing capacity: braked (kg)3.500	Turning circle (m)		12.93
Ramp angle (°)21Load compartment length (mm)1 624Load compartment width between wheelhouses (mm)1 227Load compartment height of the side walls (mm)529WeightsRoof load limit (kg) (Moving/Static)85 / 350Axle load limit front / rear (kg)1 490 / 1 959Kerb Mass (minimum) without driver and with fuel (kg)2 132Maximum payload capacity (kg) ~ based on minimum kerb mass1 148Gross Vehicle Mass (GVM) (kg)3 280Towing capacity: unbraked (kg)3 500	Ground clearance (mm) - measured under the front axle		235
Load compartment length (mm)1 624Load compartment width between wheelhouses (mm)1 227Load compartment height of the side walls (mm)529WeightsRoof load limit (kg) (Moving/Static)85 / 350Axle load limit front / rear (kg)1 490 / 1 959Kerb Mass (minimum) without driver and with fuel (kg)2 132Maximum payload capacity (kg) - based on minimum kerb mass1 148Gross Vehicle Mass (GVM) (kg)3 280Towing capacity: unbraked (kg)750Towing capacity: braked (kg)3 500	Approach / Departure angle (°) (excl. trailer hitch)		30 / 26
Load compartment width between wheelhouses (mm)1 227Load compartment height of the side walls (mm)529WeightsRoof load limit (kg) (Moving/Static)85 / 350Axle load limit front / rear (kg)1 490 / 1 959Kerb Mass (minimum) without driver and with fuel (kg)2 132Maximum payload capacity (kg) - based on minimum kerb mass1 148Gross Vehicle Mass (GVM) (kg)3 280Towing capacity: unbraked (kg)750Towing capacity: braked (kg)3 500	Ramp angle (°)		21
Load compartment height of the side walls (mm)529WeightsRoof load limit (kg) (Moving/Static)85 / 350Axle load limit front / rear (kg)1 490 / 1 959Kerb Mass (minimum) without driver and with fuel (kg)2 132Maximum payload capacity (kg) ~ based on minimum kerb mass1 148Gross Vehicle Mass (GVM) (kg)3 280Towing capacity: unbraked (kg)750Towing capacity: braked (kg)3 500	Load compartment length (mm)		1 624
WeightsRoof load limit (kg) (Moving/Static)85 / 350Axle load limit front / rear (kg)1 490 / 1 959Kerb Mass (minimum) without driver and with fuel (kg)2 132Maximum payload capacity (kg) ~ based on minimum kerb mass1 148Gross Vehicle Mass (GVM) (kg)3 280Towing capacity: unbraked (kg)750Towing capacity: braked (kg)3 500	Load compartment width between wheelhouses (mm)		1 227
Roof load limit (kg) (Moving/Static)85 / 350Axle load limit front / rear (kg)1 490 / 1 959Kerb Mass (minimum) without driver and with fuel (kg)2 132Maximum payload capacity (kg) ~ based on minimum kerb mass1 148Gross Vehicle Mass (GVM) (kg)3 280Towing capacity: unbraked (kg)750Towing capacity: braked (kg)3 500	Load compartment height of the side walls (mm)		529
Axle load limit front / rear (kg)1 490 / 1 959Kerb Mass (minimum) without driver and with fuel (kg)2 132Maximum payload capacity (kg) ~ based on minimum kerb mass1 148Gross Vehicle Mass (GVM) (kg)3 280Towing capacity: unbraked (kg)750Towing capacity: braked (kg)3 500	Weights		
Kerb Mass (minimum) without driver and with fuel (kg)2 132Maximum payload capacity (kg) ~ based on minimum kerb mass1 148Gross Vehicle Mass (GVM) (kg)3 280Towing capacity: unbraked (kg)750Towing capacity: braked (kg)3 500	Roof load limit (kg) (Moving/Static)		85 / 350
Maximum payload capacity (kg) ~ based on minimum kerb mass1 148Gross Vehicle Mass (GVM) (kg)3 280Towing capacity: unbraked (kg)750Towing capacity: braked (kg)3 500	Axle load limit front / rear (kg)		1 490 / 1 959
Gross Vehicle Mass (GVM) (kg)3 280Towing capacity: unbraked (kg)750Towing capacity: braked (kg)3 500	Kerb Mass (minimum) without driver and with fuel (kg)		2 132
Towing capacity: unbraked (kg)750Towing capacity: braked (kg)3 500	Maximum payload capacity (kg) ~ based on minimum kerb mass		1 148
Towing capacity: braked (kg) 3 500	Gross Vehicle Mass (GVM) (kg)		3 280
	Towing capacity: unbraked (kg)		750
Gross Combined Mass (GCM) (kg) 6 500	Towing capacity: braked (kg)		3 500
	Gross Combined Mass (GCM) (kg)		6 500

#### Guarantees

3-year / 120 000 km manufacturer warranty

#### Disclaimer

Dimensions, capacities and abilities apply to standard vehicles. Actual consumption will vary with vehicle loading, driving style, climatic and road conditions. The above information is effective as at January 2024 and is subject to change.

Classification:Internal and External CSD document class 8.3/ retention period: 15 years from creation Classification:Internal and External CSD document class 8.3/ retention period: 15 years from creation

Х



## **Amarok PanAmericana Specification**

A1111

PanAmericana



### **Amarok PanAmericana Specification**

New Amarok Specification	PR #	2.0 BiTDI 154kW 4Motion PanAmericana Automatic
Engine		
Cylinders		4
Capacity (cm3)		1995
Output (kW @ r/min)		154 @ 3,750
Torque (Nm @ r/min)		500 @ 1,750-2,000
CO2 emissions (g/km)		195
Transmission		
10-speed automatic (shift by wire)		Х
Performance		
Top speed (km/h)		180
Fuel consumption		
Combined		7.5
Body		
Black rear gate handle	6V3	Х
Body-colored bumper in front, X-style	2JB	Х
Dark Matte Gray bumper in rear	2K3	Х
Dark-tinted (privacy glass) rear side windows and rear window	QL5	Х
Exterior mirror housings and door handles in Dark Matte Gray	6FP	Х
Exterior mirrors, power-adjustable, heated and power-folding, with surround lighting	6XE	Х
Heated rear window	8P1	Х
Interior door handles in chrome	6JE	Х
Laminated windshield made of insulating glass	4GL	Х
_oad compartment trim in plastic with 12-V outlet in side panel	3GP	Х
Mud flaps at front and rear	6N2	Х
Powder-coated (Black) styling bar	IB4	Х
Radiator grille with chrome bezel	6KA	Х
Side steps	QT7	Х

Tie-downs on the cargo area	6B0	Х
Silver roof rails	351	Х
Underbody cladding for engine and transfer case in steel, underbody cladding for fuel tank in plastic	1SB	Х
Chassis		
4 alloy wheels "Amadora", painted Black, spare wheel (alloy rim) with original equipment tire	45P	Х
All-terrain tires 255/65 R18	84K	Х
Differential lock in rear	1Y4	Х
Part-time 4MOTION (2H, 4H, 4L)	OR3	Х
Standard suspension system	1BA	Х
Wheel locks	1PB	Х
Safety Equipment		
3 head restraints in 2nd row of seats	3Q1	Х
3-point belts in 2nd row of seats	4PP	Х
3-point belts, in addition height-adjustable in 1st row of seats	3QB	Х
Advanced high-beam control Dynamic Light Assist for IQ.LIGHT LED matrix headlamps	8G1	Х
Driver and front passenger airbags with front passenger airbag deactivation	4UF	Х
Autonomous Emergency Braking Front Assist with Pedestrian and Cyclist Monitoring	UZ3	Х
Child seat anchors ISOFIX on outer rear seats, i-Size compatible	3B5	Х
Electromechanical parking brake	UH2	Х
Electronic Stability Control and electromechanical brake booster	1AT	Х
IQ.LIGHT LED matrix headlamps	8IT	Х
LED front fog lamps	8WH	Х
LED rear combination lamps	8SK	Х
Without seat belt pretensioners in 2nd row of seats	4RA	Х
Tire Pressure Monitoring System (direct measurement)	7K3	Х
Top tether	3G3	Х
Warning signal and warning lamp for front seat belts not fastened	9P3	Х
Interior Equipment		
10-way power-adjustable driver and front passenger seats	ЗРК	Х
2 reading lights for driver and front passenger with glasses compartment in overhead console	7N2	Х
3-seater bench in 2nd row of seats	3UH	Х
Automatic transmission selector lever with shift-by-wire technology	0G2	X

Carpet floor covering	5AD	Х
Center armrest in rear on 3-seater bench	6D1	Х
Driver seat with map pocket	4U6	Х
Gearshift/selector lever knob, leather	6R2	Х
Glove compartment, illuminated and lockable	4Z3	Х
Headliner (in Ebony Black)	6NJ	Х
Leather-wrapped multi-function steering wheel	2ZU	Х
Particle filter	2V1	Х
Roof grab handles on driver side and front passenger side, rigid grab handles on A-pillar	5N3	Х
Seat heater for both seats in cab, left and right individually controllable	4A3	Х
Seats in leather Cricket	N1D	Х
Single-color ambient lighting, White	QQ1	Х
Sound system "Harman Kardon" with 8 speakers, including subwoofer and 640 W total power output	8RM	Х
Sun visor on driver and front passenger side with illuminated vanity mirror	5XA	Х
Rubber floor mats	OTG	Х
Functional Equipment		
1 USB charging socket on the interior rearview mirror	UF1	Х
120-V/230-V outlet in rear center console and in cargo area	9Z2	Х
2 vehicle keys	8QJ	Х
2-zone Climatronic air conditioning system	KH4	Х
AM/FM antenna	QVO	Х
Area View	КАб	Х
Automatic Post-Collision Braking System	7W1	Х
Central locking system with keyless locking and starting system Keyless Access with SAFELOCK	416	Х
Cruise control system with Adaptive Cruise Control ACC stop & go	8T7	Х
Digital cockpit with 31.2-cm (12.3-inch) color screen	9Q2	Х
Dynamic headlight range control	8K7	Х
Emission standard EU4	OGG	Х
Heating and fresh air system	9M0	Х
High-beam control Light Assist	8Q1	Х
Inductive charging feature	EK2	Х
Infotainment system with 30.5-cm (12-inch) color screen for navigation	18X	Х

Intermittent windshield wiper control with rain sensor	8N3	X
Lane Assist; lane keeping and lane change system, with Side Assist and trailer support	79F	× ×
LED cargo area lighting	9CW	× ×
Navigation System	7Q1	X
Park Assist with Park Distance Control in front and rear, including Rear Traffic Alert	8A2	X
Power windows in front and rear	4R1	X
Premium dashboard in leather look (vinyl)	4N3	× ×
Rear gate lockable via central locking system	3RQ	X
Removable trailer hitch, 7-pin	1D1, IP3	× ×
Dimensions / Capacities	101, 11 5	Λ
Fuel tank (l)		80
Wading depth (mm)		800
Length (mm)		5 350
Height (mm)		1 884
Width (mm)		1 910
Wheelbase (mm)		3 270
Turning circle (m)		12.93
Ground clearance (mm) - measured under the front axle		235
Approach / Departure angle (°) (excl. trailer hitch)		30 / 26
Ramp angle (°)		21
Load compartment length (mm)		1 624
Load compartment width between wheelhouses (mm)		1 227
Load compartment height of the side walls (mm)		529
Weights		
Roof load limit (kg) (Moving/Static)		85 / 350
Axle load limit front / rear (kg)		1,490/ 1,959
Kerb mass (minimum) without driver and with fuel (kg)		2 175
Maximum payload capacity (kg) ~ based on minimum kerb mass		1 105
Gross Vehicle mass (GVM) (kg)		3 280
Towing capacity: unbraked (kg)		750
Towing capacity: braked (kg)		3 500
Gross Combined mass (GCM) (kg)		6 500

#### Guarantees

3-year / 120 000 km manufacturer warranty

#### Disclaimer

Dimensions, capacities and abilities apply to standard vehicles. Actual consumption will vary with vehicle loading, driving style, climatic and road conditions. The above information is effective as at January 2024 and is subject to change.

Classification:Internal and External CSD document class 8.3/ retention period: 15 years from creation Classification:Internal and External CSD document class 8.3/ retention period: 15 years from creation

Х



dille v

PanAmericana

a sum

## **Amarok Aventura Specification**

m

Aventura



Commercial Vehicles

\*Local specification differs from model shown

New Amarok Specification	PR #	2.0 BiTDI 154kW 4Motion Aventura Automatic
Engine		
Cylinders		4
Capacity (cm3)		1995
Output (kW @ r/min)		154 @ 3,750
Torque (Nm @ r/min)		500 @ 1,750-2,000
CO2 emissions (g/km)		195
Transmission		
10-speed automatic (shift by wire)		Х
Performance		
Γop speed (km/h)		180
Fuel consumption		
Combined		8.4
Body		
Black bumper in rear with chrome-plated styling elements	2K1	Х
Body-colored bumper in front, X-style	2JB	Х
Body-colored rear gate handle	6V2	Х
Chrome-plated exterior mirror housings and door handles	6FD	Х
Dark-tinted (privacy glass) rear side windows and rear window	QL5	Х
exterior mirrors, power-adjustable, heated and power-folding, with surround lighting	6XE	Х
oad compartment cover with power roll system and cargo area management system	3U7, 6L6	Х
leated rear window	8P1	Х
nterior door handles in chrome	6JE	Х
aminated windshield made of insulating glass	4GL	Х
oad compartment trim in plastic with 12-V outlet in side panel	3GP	Х
Aud flaps at front and rear	6N2	Х
Radiator grille with chrome bezel	6KA	Х
ide steps with chrome inserts	QT8	Х

Sports bar	IB1	Х
Tie-downs on the cargo area	6B0	Х
Silver roof rails	351	Х
Underbody cladding for engine and transfer case in steel, underbody cladding for fuel tank in plastic	1SB	Х
Chassis		
255/55 R20 110V tires	83A	Х
4 alloy wheels "Bendigo" 8 x 20, spare wheel (alloy rim) with original equipment tire	40T	Х
Part-time 4MOTION (2H, 4H, 4L)	0R3	Х
Differential lock in rear	1Y4	Х
Standard suspension system	1BA	Х
Wheel locks	1PB	Х
Safety Equipment		
3 head restraints in 2nd row of seats	3Q1	Х
3-point belts in 2nd row of seats	4PP	Х
3-point belts, in addition height-adjustable in 1st row of seats	3QB	Х
Advanced high-beam control Dynamic Light Assist for IQ.LIGHT LED matrix headlamps	8G1	Х
Driver and front passenger airbags with front passenger airbag deactivation	4UF	Х
Autonomous Emergency Braking Front Assist with Pedestrian and Cyclist Monitoring	UZ3	Х
Child seat anchors ISOFIX on outer rear seats, i-Size compatible	3B5	Х
Electromechanical parking brake	UH2	Х
Electronic Stability Control and electromechanical brake booster	1AT	Х
IQ.LIGHT LED matrix headlamps	8IT	Х
LED front fog lamps	8WH	Х
LED rear combination lamps	8SK	Х
Tire Pressure Monitoring System (direct measurement)	7K3	Х
Top tether	3G3	Х
Warning signal and warning lamp for front seat belts not fastened	9P3	Х
Interior Equipment		
10-way power-adjustable driver and front passenger seats	3PK	Х
2 reading lights for driver and front passenger with glasses compartment in overhead console	7N2	Х
3-seater bench in 2nd row of seats	3UH	Х

Automatic transmission selector lever with shift-by-wire technology	0G2	Х
Carpet floor covering	5AD	Х
Center armrest in rear on 3-seater bench	6D1	Х
Driver seat with map pocket	4U6	Х
Gearshift/selector lever knob, leather	6R2	Х
Glove compartment, illuminated and lockable	4Z3	Х
Headliner (in Ebony Black)	6NJ	Х
Leather-wrapped multi-function steering wheel	2ZU	Х
Particle filter	2V1	Х
Roof grab handles on driver side and front passenger side, rigid grab handles on A-pillar	5N3	Х
Seat heater for both seats in cab, left and right individually controllable	4A3	Х
Seats in leather Savona	N2M	Х
Single-color ambient lighting, White	QQ1	Х
Sound system "Harman Kardon" with 8 speakers, including subwoofer and 640 W total power output	8RM	Х
Sun visor on driver and front passenger side with illuminated vanity mirror	5XA	Х
Velour floor mats (Premium with lettering "Aventura")	OTN	Х
Functional Equipment		
1 USB charging socket on the interior rearview mirror	UF1	Х
120-V/230-V outlet in rear center console and in cargo area	9Z2	Х
2 vehicle keys	8QJ	Х
2-zone Climatronic air conditioning system	KH4	Х
AM/FM antenna	QVO	Х
Area View	КАб	Х
Automatic Post-Collision Braking System	7W1	Х
Central locking system with keyless locking and starting system Keyless Access with SAFELOCK	416	Х
Cruise control system with Adaptive Cruise Control ACC stop & go	8T7	Х
Digital cockpit with 31.2-cm (12.3-inch) color screen	9Q2	Х
Dynamic headlight range control	8K7	Х
Emission standard EU4	OGG	Х
Heating and fresh air system	9M0	Х
High-beam control Light Assist	8Q1	Х

Inductive charging feature	EK2	Х
Infotainment system with 30.5-cm (12-inch) color screen for navigation	18X	Х
Intermittent windshield wiper control with rain sensor	8N3	Х
Lane keeping system Lane Assist and lange change system Side Assist incl. trailer support	79F	Х
LED cargo area lighting	9CW	Х
Navigation System	7Q1	Х
Park Assist including Park Distance Control in front and rear including Rear Traffic Alert	8A2	Х
Power windows in front and rear	4R1	Х
Premium dashboard in leather look (vinyl)	4N3	Х
Rear gate lockable via central locking system	3RQ	Х
Removable trailer hitch, 7-pin	1D1, IP3	Х
Dimensions / Capacities		
Fuel tank (l)		80
Wading depth (mm)		800
Length (mm)		5 350
Height (mm)		1 884
Width (mm)		1 910
Wheelbase (mm)		3 270
Turning circle (m)		12.93
Ground clearance (mm) - measured under the front axle		234
Approach / Departure angle (°) (excl. trailer hitch)		30 / 26
Ramp angle (°)		21
Load compartment length (mm)		1 624
Load compartment width between wheelhouses (mm)		1 227
Load compartment height of the side walls (mm)		529
Weights		
Roof load limit (kg) (Moving/Static)		85 / 350
Axle load limit front / rear (kg)		1,490/ 1,785
Kerb Mass (minimum) without driver and with fuel (kg)		2 248
Maximum payload capacity (kg) ~ based on minimum kerb mass		942
Gross Vehicle Mass (GVM) (kg)		3 190
Towing capacity: unbraked (kg)		750

Towing capacity: braked (kg)	3 500
Gross Combined Mass (GCM) (kg)	6 400
Guarantees	
3-year / 120 000 km manufacturer warranty	Х
Disclaimer	
Dimensions, capacities and abilities apply to standard vehicles. Actual consumption will vary with vehicle loading, driving style, climatic and road conditions. The above information is effective as at January 2024 and is subject to change.	

Classification:Internal and External CSD document class 8.3/ retention period: 15 years from creation Classification:Internal and External CSD document class 8.3/ retention period: 15 years from creation



Aventura

Commercial Vehicles

\*Local specification differs from model shown

min